

# Ethernet Converter PC-E



## Description:

This type of Ethernet converter / Gateway is capable to link any serial (RS-232 or RS485) devices to your computer network via Ethernet for access control or remote control and monitoring purposes.

## Features:

- Serial to Ethernet communication
- DIN Rail/Panel Mount
- COM1: RS232/RS485, RJ45 for Ethernet connectivity
- Application: Connects IO modules, controllers, HMI with Ethernet Network
- Function: Transparent data link or Gateway to convert Modbus RTU to Modbus TCP messages
- Support Multiple sockets enables up to 4 Masters to communicate with slaves connected to PC-E converter
- Web server for Configuration

## Technical Specification:

- Power Supply: 90mA @ 10VDC / 40mA @ 26VDC
- Ethernet: 10/100 Mbits, Connector RJ45
- Serial: RS232, 3 Wire, TX, RX & GND  
RS485, 2 Wire Multi drop twisted pair  
Baud Rate 2400, 4800, 9600, 19200, 38400, 57600, 115200
- Communication Settings:  
Data Bits: 5, 6, 7, 8  
Parity None, Even, Odd  
Stop Bits 1, 2.
- Operating Temperature: -10°C to + 50°C
- Storage Temperature: -40°C to + 85°C
- Connectors: Power and Communication: 8 way screw connector
- Protection class: IP20
- Humidity: Up to 95% non-condensing

# ***BrainChild***

**BRAINCHILD Electronic Co., Ltd**

No. 209 Chung Yang Rd., Nangang Dist.

Taipei, Taiwan

Tel: 886-2-27861299, Fax: 886-2-27861395

Email: [sales@brainchild.com.tw](mailto:sales@brainchild.com.tw)

Website: <http://www.brainchild.com.tw>